



HTC-1462T MODEL

# INDUSTRIAL GRINDERS

Visit our Website  
for further HogZilla Info.  
[www.hogzilla.com](http://www.hogzilla.com)



HC-1462P MODEL



HC-1462P MODEL



HTC-1464T MODEL



HTC-1464T MODEL  
W/ OPTIONAL TIRE  
GRINDING PACKAGE

The HC series grinders are built to be the most reliable high capacity grinders in their class. You can expect maximum production at the end of the day, be it acres, tons, or yards of material being ground. At 750 to 1050 horsepower and 88,000lbs., they can handle your toughest jobs and last for years doing it. The power is delivered to the hammermill by a Hydraulic Coupling or an optional Torque Converter which multiplies the engine torque to the hammermill for even greater production. The HC series is available in fifth-wheel portable, self-loading, & track driven models.

# HOGZILLA SERIES

# HogZilla Industrial Grinders

## The Heavyweight of Waste Reduction

The HC series offers standard features not found in other large machines. Available in Portable, Track Mounted and Knuckle-Boom Loader configurations; the correct model is available for all situations requiring a high capacity grinder. Compare the reliability and productivity to other grinders in its class. The HC series grinders are heavy weights with BIG appetites. The solid construction of the HC Series is a definite requirement for years of successful operation on the toughest waste reduction jobs.



HC-1462L MODEL



A Voith Turbo Hydraulic Coupling transfers power from the engine to the hammermill. An optional Torque Converter multiplies engine torque for greater production. The fluid drive protects engine from hammermill shock. A heavy duty driveshaft couples the engine to the hammermill.

### Production Rates (tons per hour)\* See Below

Yardwaste ..... 100-180  
Stumps & Logs.....50-110  
Pallets/C&D Waste...35-110

### Standard Equipment

Fluid Coupling Drive  
Radio Remote Control  
Oversized Radiator Precleaner Enclosure  
Engine Enclosure  
Vandalism Lock Package  
Auxiliary Power Unit includes:  
10HP Diesel Engine  
Air Compressor  
Service Hydraulic Pump  
50ft Air Hose and Reel  
Hydraulic Rod Puller  
Lockable Tool Boxes

**HC SERIES**

### Optional Equipment

Torque Converter Drive  
Track Drive  
North Shore or Prentice 180E Loader  
Mesabi or Glacier Radiator  
Side-Slide Thrown Object Restraint  
Bolt-In Tire Grinding Package  
Radial Stacking Elevator

\*Rates will vary with input material characteristics, discharge material requirements, machine set up, machine options selected, & operating procedures.

Represented by:

HCS02162010 Supercedes HCS06232009

HC Series Specifications		HC-1462P	HC-1462L	HTC-1464T
Horsepower	Cat	820 - 1050	820 - 1050	1050(Standard)
	Cummins	760 - 1050	760 - 1050	750-1050
	Detroit	760 - 1005	760 - 1005	760-1005
Hammer-Swing		31" x 62"	31" x 62"	38" x 64"
Screen Area		3813 sq. in.	3813 sq. in.	4610 sq. in.
Screen Thickness		1"	1"	1"
Hammer Weight		50 lbs.	50 lbs.	80 lbs.
Hammer Number		28	28	24 - 48
Rod Diameter		2"	2"	3"
Tub Top Width		14'	14'	14'
Conveyor Belt or Augers		42"	42"	48" or 3 ea. 14" Augers
Elevator Belt		36"	36"	48"
Trans. Width		11' - 11"	11' - 11"	11' - 11"
Trans. Length		48' - 6"	50' - 4"	45'
Total Weight	(Approx. Per Options: Tracks, Loader, Throw Restraint, etc.)	85 - 94,000 lbs.	92 - 94,000 lbs.	104 - 108,000 lbs.

Specifications subject to change without notice. As improvements are made, actual product offered for sale may vary in design.



**CW MILL EQUIPMENT CO., INC.**  
14 Commerce Drive - Sabetha, Kansas 66534  
(785) 284-3454 FAX (785) 284-3601  
(800) 743-3491 EMAIL: hogzilla@cwmill.com  
Visit our Web Site at www.hogzilla.com