



HORIZONTAL GRINDER



Visit us at
www.hogzilla.com
for more details.

Horizontal Standard Features -
Hydraulic Clutch Drive
Hydraulic Opening Mill Box Hood for
easy Screen replacement.
Remote Control Unit

Infeed System (Standard) -
62" wide x 50" tall Mill Infeed Opening
62" wide x 20' long Infeed Conveyor
40" Diameter Single Infeed Wheel
46" Swing TC-Series Hammermill

Discharge System (Standard) -
60" wide Belt on Belly & 48" side Belt
on Discharge Stacking Conveyor

Horizontal Optional Features -
Electric Power
Torque Converter (Upgrade)
Diesel Powered auxiliary engine for
service hydraulics
Compressed Air System
Rod Push/Pull System
Thrown Object Restraint System
Fire Suppression System

Infeed System Options -
36", 38", 46", or 52" Diameter Mill Pkgs.
Hammermill with 12 each 3" pins
on 8 3/4" diameter Shaft

Discharge System Options -
25 Degree Radial Staking Elevator
Magnetic Head Pulley



HORIZONTAL
SERIES

HogZilla's Horizontal (HZL) Series Grinders are designed to put CW Mill Equipment's long and successful experience in industrial grinders to work building the industry's best horizontal wood grinder.

HZL Series Grinders are built with same commitment to reliable performance that HogZilla has provided with its tub grinders for decades. By providing similar features including over-sized components, solid construction, and production oriented design, the HZL Series lives up to HogZilla's Monster reputation.

The HZL Series can be configured in stationary, portable, or track mounted arrangements with engine choices ranging from 400hp to 1,000hp. The HZL can be equipped with a variety of different mill drive systems including Wet Clutch, Hydraulic Coupling, or Torque Converter. The HZL Series also provides several choices in hammer mills, feeder sizes, and styles allowing the grinder to be custom built for the end user.

SOME OF THE MANY HZL SERIES STANDARD FEATURES AND OPTIONS

- Choice of grinder configurations including stationary, pintle hitch portable, fifth wheel hitch portable, and track mounted
- Choice of suspensions on portable units including super-single triple axle, dual tire triple axle, and 16-tire tandems for West Coast
- Choice of 750-1,000hp (Any major engine manufacturer)
- Choice of Mill Drives including Wet Clutch, Hydraulic Coupling, or Torque Converter
- Choice of Hammer Mill Configurations
- Compressed air system w/ maintenance support kit
- Hot Vulcanized Continuous Conveyor & Elevator Belts
- Radial Stacking Elevator
- Single 44" Feed Wheel
- Remote Control
- Auxiliary service hydraulics
- Choice of feeder system including drag chain, rubber belt, and metal-pan belt
- Legal shipping width on units up to 750hp & 11'-11" shipping width on units over 860hp
- Total machine weights ranging from approx. 80,000 lbs. to 120,000 lbs.

- Other HZL sizes available.
 - 400hp to 750hp with legal shipping width.
 - Units over 1200hp available through special order.



HZL-6250P Specifications

Engine (CAT, Cummins, or Detroit)	
Horsepower	750 - 1200
Operational Length	59'
Transport Length	41'
Transport Height	13' 4"
Width	11' 11"
Gross Weight (Varies with Options)	80,000-120,000#
Tires	Dual 275/70R 22.5
Fuel Capacity	500 gallons
Hydraulic Oil Capacity	150 gallons

Specifications subject to change without notice. As improvements are made, actual product offered for sale may vary in design.



CW MILL EQUIPMENT CO., INC.

14 Commerce Drive - Sabetha, KS 66534
 Phone (785) 284-3454 or (800) 743-3491
 Send us an Email hogzilla@cwmill.com
 Fax (785) 284-3601
 Visit us on the web www.hogzilla.com



Represented by: